

# Quick Guide

## 4K Flex Lightsystem

**Specifications:**

- Material: T6061 aluminum with hard anodized surface
- Light Source: XHP70, LED chip lifespan 50,000 hours
- Luminous Output: 4,000 lumens
- Color Temperature: 6,000K
- Beam Angle: 8° spot
- Depth Rating: 150 m / 450 ft

**Switch Type: Magnetic**

- Modes: 100% - 50% - 15%

**Burntime with 3.5Ah battery:**

- 60 min (100%)
- 140 min (50%)
- 600 min (15%)

**Runtime with 14Ah battery:**

- 240 min (100%)
- 600 min (50%)
- 2400 min (15%)

**Weight:**

- Net Weight: Handheld lamp 700 g including battery
- Net Weight: Tank lamp 14Ah 1900 g including battery

**Battery Type:**

Handheld battery: 3 x 18650 Li-Ion

14Ah battery tank: 12 x 18650 Li-Ion

**Instructions:**

- To turn the light on or off, hold the button for 2-3 seconds.
- To change brightness levels, hold the button for 1 second.
- When the battery is low, the light will flash every 30 seconds.

**Maintenance and Storage:**

- Rinse the light with fresh water after each use.
- Regularly check the O-rings for cleanliness and damage; replace them annually.
- Store the Li-Ion battery in a clean, dry location.
- Charge or discharge the battery every 2-3 weeks to maintain battery life.

**Warnings:**

- Do not shine the light directly into eyes.
- Do not use the light above water to avoid overheating.
- Do not open the housing underwater.

**Warranty:**

- LED lamp head: 1-year warranty
- Battery and charger: 6-month warranty

**The warranty does not cover:**

- Loss or damage of the light
- Surface scratches or normal wear and tear
- Damage from sunlight, heat, or corrosive chemicals
- Overheating due to improper use
- Malfunctions due to insufficient maintenance, improper use, modifications, or negligence.

**The 4K Flex system and electronic accessories are manufactured in accordance with the following standards**

- EN IEC 55015:2019+A11:2020
- EN IEC 61000-3-2:2019+A1:2021+A2:2024
- EN 6100-3-3:2013+A1:2019+A2:2021+AC:2021-01
- EN IEC 61547:2023



You can find a complete version of the manual via the QR code.

